

		<p align="center"><u>KORMOS IMPEX SRL ROMÂNIA</u> Headquarters: B-dul N. Titulescu 119, room 1, Sector 1, Bucuresti, Workstation: Str. Cpt. Teodorescu 3, Com. Vișina, Jud. Dambovița, A1 Bucuresti - Pitești Km 70, Tel/fax 0245.725.221/0245.725.222 Mobile 0722.296.143, www.kormos.ro, www.kormos-parchet.ro kormosimpexsrl@yahoo.com, office@kormos-parchet.ro J40/3070/2000, RO12892191, RO05BUCU1252234332020RON ALPHA BANK</p>	
---	---	---	---

TEHNICAL DATA SHEET CHEVRON PARQUET

1. GENERAL CHARACTERISTICS

CHEVRON PARQUET FLOORING is a product manufactured by KORMOS IMPEX SRL. of oak (Quercus spp. QCXE code) from its own forestry exploitation in Romania. Romanian oak is a hardwood species with high durability against the action of aggressive factors. The Chevron Parquet Flooring is made with tongue & groove joint, with bevelled edges on all sides, with 45 ° end cuts and delivered unfinished. Defined as a special "Hungarian point" installation pattern, according to SR EN 13756 Terminology.

2. FIELD OF USE

CHEVRON PARQUET FLOORING is used for interior floors, heavy traffic, with superior selectivity requirements for outstanding design, remarkable technical performance, reliability, durability, thermal and acoustic comfort, eco-sanogenic properties.

3. TECHNICAL QUALITY CONDITIONS

Quality standard: SR EN 13226:2009 Wood floors. Elements of solid wood floor with tongue & groove joint.

Quality Grade	EXTRA: Allows all textures on the upper face of the floor board, some knots up to 4 mm in diameter if they are small and healthy. No sapwood. Relatively uniform colors.
	NATUR: On the upper face allows sound knots up to 10 mm, variation of colors, possible surface cracks, in some elements sapwood is allowed for max. 20% of the floor board.
	BR: On the upper face, allows sound knots up to 20 mm in diameter on floor boards up to 120 mm wide and up to 40 mm on floor boards from 130 to 170 mm wide, sapwood, coloration. Unfinished floors: open knots. Finished floors: filled knots.
	EXTRA D: Allows knots up to 4 mm, coloration
Dimensions, mm	Thickness 21mm; Width 90 mm; Length 510 mm.
Deviations, mm	±0,2 thickness ; ±0,5 length ; ±0,2 width ; (+0,3...0) groove depth ; (+0...0,3) tongue width ; 0,1 ≤ groove thickness-tongue thickness ≤ 0,4
Moisture content, %	7...11
Durability	Class S (susceptible)-insects, class 2 (good)- fungus (SR EN 350). Needs protection (SR EN 460).
Warranty, years	20/EXTRA, 20/NATUR, 20/BR, 20/EXTRA D, installed and maintained properly, excluding natural durability.
Storage & Exploitation	18-25°C, RH 45-60%.
Installation & Maintenance	According to Installation Guide & Maintenance Guide.

4. CERTIFICATION STANDARDS

SR EN 14342:2013 Wood floors and parquet flooring. Characteristics, conformity assessment and marking.

FSC-STD-40-004 FSC v3.0 Standard for Chain of Custody Certification.



